


Tile with the modular size of 600 x 600 mm is produced with edge A, B, D2 og E.

Surface :	Gyptone Point 12 is supplied pre-painted white NCS 0500, in design with edge A, D2 and E15, all with a gloss value of 5-9. Point 12 with edge B is supplied unpainted.
Design:	Gyptone Point 12 is based on a 12,5 mm thick Gyproc plasterboard for edge D2 and B. For the edge A and E, the board is 10 mm thick. Perforated area: 5 % The tile is perforated with holes 6,5 mm in diameter, cc15 mm.
Technic:	Gyptone products with edge B og D2 is produced according to the drawing. Gyptone products with edge A is produced 6 mm and edge E 8mm shorter than the standard module, in length and width. The weight is approximately 8 kg/m <sup>2</sup> for 12,5 mm and 7 kg/m <sup>2</sup> for 10 mm board.



Perforation

**GYPTONE POINT 12**

 <p>GYPROC A/S HARESKOVVEJ 12 4400 KALUNDBORG TLF. + 45 59 57 03 30 SAINT-GOBAIN FAX. +45 59 57 03 01</p>	Drawn by <b>JFP</b>	Date <b>03.08.2007</b>	Drawing No.  <b>P12</b>
	Measure <b>1:10</b>	REV. DATO: <b>22.04.2015</b>	